



ClimaDry Dehumidifier 705 pints per day

Commercial dehumidifier, 115 volt, no heat added to space. Connects to standard 230 volt outdoor 5 ton air conditioner condenser.

Details

This all aluminum, commercial-grade air conditioner and dehumidifier removes over 700 pints of water per day from air in your building. The unit was designed for growers with the help of ClimaGrow R&D. Dry air is supplied at near 70 degrees Fahrenheit. A detachable humidistat allows you to set the desired humidity level.

Specifications

Dimensions	47"D x 42"L x 27"H
Weight	300 pounds
Power	115V, single-phase
Amperage	4.4 amps
Warranty	one year

Water Removal per day

705 pints	80°F, 60%rh
------------------	-------------

**PROVIDES COOL 65 TO 75F
AIR AND DEHUMIDIFICATION
FROM ONE UNIT**

Features

- ◆ Thermostat controlled cooling
- ◆ Humidistat controlled drying
- ◆ Stainless steel: drain pan and 3/4 inch drain coupling
- ◆ 1,000 cfm (nominal) supply air blower
- ◆ Quiet operation, low static (ductable)
- ◆ Made in the USA
- ◆ Designed for commercial use
- ◆ Auto defrost allows operation in cool buildings
- ◆ HVAC technician friendly design
- ◆ Connects to standard 230 volt, 5 ton outdoor condenser unit
- ◆ 2-inch pleated MERV 3 through 11 air filter compartment
- ◆ Aluminum skid with forklift pockets and corner eyes
- ◆ Cabinet constructed from pre-painted aluminum sheet metal
- ◆ Reheat condenser delivers air near room temperature



Warranty Information

Limited Warranty: One year warranty on any defective parts.

Limitation of Liability: To the extent allowable under applicable law, Subcooled Air's liability for consequential and incidental damages is expressly disclaimed. Subcooled Air's liability in all events is limited to and shall not exceed the cost of repair. Shipping damage is not covered under warranty.