



## Subcooled 705 Dehumidifier (Climadry705)

- Commercial dehumidifier
- Removes 705 pints of water per day (AHAM conditions: 80F, 60% rh)
- 115 volt
- Dual supply air temperature
- Connects to standard 5 ton air conditioner condenser.



PROVIDES COOL OR  
WARM, DRY AIR FOR  
INDOOR HUMIDITY  
CONTROL

### Subcooled 705 Dehumidifier

This all aluminum, commercial-grade dehumidifier removes up to 705 pints of water per day (AHAM conditions; 80F, 60%rh) from air in your building. Dual temperature provides cool or warm dry air from one unit. A wall mounted humidistat allows you to set the desired room humidity level.

### Specifications

<b>Dimensions</b>	47"D x 42"L x 27"H
<b>Weight</b>	300 pounds
<b>Power</b>	115V, single-phase
<b>Amperage</b>	4.8 amps
<b>Warranty</b>	one year

### Features

- ◆ Humidistat controlled drying
- ◆ Stainless steel: drain pan and 3/4 inch drain coupling
- ◆ 1,000 cfm (nominal) supply air blower
- ◆ Quiet operation, low static (ductable)
- ◆ Made in the USA
- ◆ Designed for commercial use
- ◆ Auto defrost allows operation in cool buildings
- ◆ HVAC technician friendly design
- ◆ 2-inch pleated MERV 3 through 11 air filter compartment
- ◆ Aluminum skid with forklift pockets and corner eyes
- ◆ Cabinet constructed from pre-painted aluminum sheet metal
- ◆ Thermostat controlled reheat delivers cool or warm air

### Warranty Information

**Limited Warranty:** One year warranty on any defective parts.

**Limitation of Liability:** To the extent allowable under applicable law, Subcooled Air's liability for consequential and incidental damages is expressly disclaimed. Subcooled Air's liability in all events is limited to and shall not exceed the cost of repair. Shipping damage is not covered