



## Subcooled 550 Hybrid Dehumidifier



An all aluminum, commercial-grade air conditioner and dehumidifier removes 550 pints of water per day and delivers three (3) tons of cooling to the room. When room temperature drops, reheat switches to warm, dry supply air.

### Specifications

<b>Dimensions</b>	25.4"D x 52"L x 22"H
<b>Weight</b>	170 pounds
<b>Power</b>	115 or 230V, single-phase
<b>Amperage</b>	8.0 / 4.0 amps
<b>Warranty</b>	one year on defective parts

### Warranty Information

**Limited Warranty:** One year warranty on any defective parts.

**Limitation of Liability:** To the extent allowable under applicable law, Subcooled Air's liability for consequential and incidental damages is expressly disclaimed. Subcooled Air's liability in all events is limited to and shall not exceed the cost of repair. Shipping damage is not covered under warranty.

All information contain here within is subject to revision  
by Subcooled Air 01/2023

- Removes 550 pints of water per day (AHAM conditions: 80F, 60% rh) and 420 pints per day @ 75F, 50% relative humidity
- Three (3) tons of sensible cooling (lights-on conditions)
- Warm temperature air, 80 degrees F (lights-off conditions)
- Connects to standard 14 SEER, R-410a, 5 ton air conditioner condenser.
- 24 volt environmental controller friendly

## REDUCE HEAT LOAD

### Features

- ◆ Humidistat or 24 volt controller operated
- ◆ Galvanized steel: drain pan and 3/4 inch drain coupling
- ◆ 1,300 cfm (nominal) supply air blower
- ◆ Quiet operation, low static
- ◆ Made in the USA
- ◆ Designed for commercial use
- ◆ Auto defrost allows operation in cool buildings
- ◆ Connects to 5 ton, 14 SEER, R-410a a/c condenser
- ◆ 2-inch pleated MERV 8 air filter
- ◆ Pre-painted aluminum sheet metal cabinet
- ◆ Reheat switches to warm air during lights-off



**Subcooled AIR**